

TEST REPORT

Technical Report: (6817)150-0043 June 10, 2017

Date Received: May 29, 2017 Page 1 of 3

Factory Company Name: Newage Apparels Ltd.

Factory Address: Nischintopur, Purbo Norshinghpur, Zirabo, Savar, Dhaka-1341, Bangladesh.

Client: H&M

Initiated By H&M Initiated Sample Type: Grab Sample* Sample Pick Up Date: May 29, 2017

Test Period: May 29, 2017 to June 10, 2017

Sample Description: Sample(s) received is/are stated to be:

I001) Wastewater after treatment (ETP Outlet)

REMARK

This report shown the test result of the environment sample(s) of above factory which collected on specific date and time. The result(s) of this report shall not be used for any regulatory compliance purposes.

* The grab sampling is agreed with client.

BUREAU VERITAS
CONSUMER PRODUCTS SERVICES (BANGLADESH) LTD.

M. NUR ALAM

SENIOR MANAGER

ANALYTICAL LABORATORY

E-mail: bvcps.bd@bd.bureauveritas.com



Technical Report:

(6817)150-0043 June 10, 2017 Page 2 of 3

Sampling

Method of sampling used is grab sampling (agreed with client.). Grab samples are discrete samples that are taken at a location to provide a 'snapshot' of the water quality characteristics at that time. For the purposes of quantifying water or wastewater constituents, grab samples will show the concentrations at that location and time of sampling. They will not provide any information about the concentrations outside that point in time.

Remark:

- Sampling procedure is with reference to below standards:
 - 1) South Australia EPA Guidelines (June 2007), Regulatory Monitoring and Testing Water and Wastewater Sampling.
 - 2) Australia EPA (Victoria) Guideline (June 2009), Sampling and Analysis of Waters, Wastewaters, Soils and Wastes.
 - 3) ISO 5667-3:2003, Water Quality Sampling Part 3: Guidance on the Preservation and Handling of Water Samples.
 - 4) ASTM D3976-92 (Reapproved 2010), Standard Practice for Preparation of Sediment Samples for Chemical Analysis.
- Field data records are attached in Appendix

Tested Item(s) : I001) Wastewater after treatment (ETP Outlet)

Test Parameter	Result	Unit	Test Method	
Tested Item(s)	I001	-	-	
pH Value	6.4 at 23°C	-	APHA 4500-H ⁺ B:2012 & U. S. EPA 150.2	
Total Suspended Solids (TSS)	41	mg/L	APHA 2540 D:2012	
Chemical Oxygen Demand (COD)	60	mg/L	APHA 5220 B:2012 & U. S. EPA 410.3	
Biochemical Oxygen Demand (BOD ₅)	10	mg/L	APHA 5210 B:2012	

BDL: Below Detection Limit, D.L: Detection Limit.


Detection Limit (mg/L): 5 (TSS), 2 (COD), 2 (BOD₅).

APHA: American Public Health Association Standard Methods for the Examination of Water and Wastewater.

U. S. EPA: United States Environmental Protection Agency.

°C: degree Celsius, mg/L: milligram per liter.

Photo of the Sample/Sampling Location





Technical Report:

(6817)150-0043 June 10, 2017 Page 3 of 3

APPENDIX

	Version: August 2014.		4	Z///		,	
	1. Basic Data	Wisckinto Savara nt (Olological) Chi chi	GE APPI apur Pu	or)	UD. visinghay Printing	ur, Br	the.
	Criteria	inlet		utlet			
	Pktures laken (Pes/Ila)						
	Teniperature:	<u> </u>	320	'c			
	Visual Color:		Coloni	255			ļ
	Rame of the Lab:		OVCPS.				.
-	bate and time of samplings		29,	05/3			
	Oate of submitting:		29.0	5.17		•	
	Sampling equipment provided by:		NOPS		·		
	Comments:		,		,		
·	Observation on ETP Operations						
M).	Name and signature HEHTCHUI SSLAM		0.05.13			. !	
					٠,		
		ENQ					
			END				